



CABLECAST SX LE

BROADCAST VIDEO SERVER

The Cablecast SXLE is a multi-format video server using a state-of-the-art broadcast architecture to bring you unheard of performance at an unbeatable price. The SXLE gives you two output channels and one encoder channel of MPEG-2 quality at up to 15Mbps. Multi-format means that you can also play DVCPRO, DVCAM, QuickTime, Windows Media 9 and MPEG-4 H.264 directly from the SXLE. The SXLE also comes complete with Cablecast scheduling and automation software and the Carousel Framework, providing you a path toward a complete channel solution.



DIGITAL SIGNAGE & BROADCAST

tightrope media systems



WHY USE THE CABLECAST SXLE?

- :: Unbeatable price/performance benchmarks
- :: The same great Cablecast programming and automation software that gives you complete control of your facility from any location with an internet connection (see Cablecast brochure)
- :: No need to transcode everything to MPEG-2, you can play native file formats, and you get Cablecast's unparalleled deck and device control
- :: Attaches to your network for easy data transfer from editing stations and external storage
- :: Import files directly from DVDs up to six times faster than real time with DVD import utility
- :: Includes internal storage, and you can play directly from external storage devices
- :: Easily share and play files from other facilities (MPEG-2, H.264, QuickTime, Windows Media 9)*



KEY FEATURES

- :: Two output channels and one encoder channel
- :: Plays MPEG-2, MPEG-4, H.264, Windows Media 9, QuickTime, DV25, DVCPRO and DVCPRO50*
- :: Includes the Carousel Framework. Add up to three Cablecast CG250s for up to three channels of community bulletin board
- :: Complete Cablecast programming and automation software included
- :: DVD import utility included
- :: Integrated with Cablecast streaming and internet VOD servers (Optional)
- :: Plays MPEG-1, Layer 2 and Linear PCM
- :: Optional 4:2:2 and I-Frame MPEG-2 encoding
- :: Optional SDI input and output, composite included

CABLECAST SXLE SPECS

Network:	10/100/1000base-TX
Power:	100-240V AC, 50/60Hz
Power Consumption:	250w nominal
Dimensions:	19" x 22" x 3.5" (2RU)
Weight:	34lbs. (Shipping)
Hard Disk:	500GB
Video Inputs:	Composite: BNC x 1
Audio Inputs:	Analog: XLR x 2 (1 pair)
Video Outputs:	Composite: BNC x 2
Audio Outputs:	Analog: XLR x 4 (2 pair)
Genlock:	Analog black burst: BNC x 1
Encoding formats:	MPEG-2 IBP: 4:2:0 - 4-15Mb/s
Playback Formats:*	DV, DVCAM, DVCPRO, DVCPRO50, MPEG-2 4:2:0, MPEG-2 4:2:2, MPEG-2 I frame, Windows Media 9, Quicktime

*Some restrictions apply

Tightrope Media Systems . 800 Transfer Rd, Suite 1B . Saint Paul, MN . 55114  866 866-4118  612 866-4110  www.trms.com

©2009 Tightrope Media Systems Corporation. All rights are reserved. Cablecast and Front Door are either registered trademarks or trademarks of Tightrope Media Systems in the United States and/or other countries. Other products and company names mentioned herein may be trademarks of their respective owners. Tightrope Media Systems reserves the right to make changes to specifications at any time and without prior notice. The information contained herein is believed to be accurate and reliable, however no responsibility is assumed by Tightrope Media Systems for its use, nor any infringement of patents or rights of third parties resulting from its use. Printed in the USA.

